

Application No. 09/908070  
Page 2

Amendment  
Attorney Docket No. S63.2B-9826-US01

**Amendments To The Claims:**

1. (Currently Amended) A method for detecting the presence and uniformity of a lubricious coating on a medical device comprising the steps of:
  - a) preparing a mixture of at least one fluorescing agent which is a xanthene, a triarylmethane or mixture thereof and at least one lubricant;
  - b) applying said mixture to the surface of a medical device to form a coating capable of exhibiting fluorescence; [[and]]
  - c) subjecting the surface of the medical device to a source of energy capable of inducing a fluorescent emission; and
  - d) observing the fluorescent emission to determine the location, uniformity or both of said lubricant.
2. (Canceled)
3. (Previously Presented) The method of claim 1 wherein said fluorescing agent is a fluorescein, a rhodamine, a derivative thereof, [[and]] or mixture thereof.
4. (Previously Presented) The method of Claim [[1]] 39 wherein said fluorescing agent is a hydrophilic [[dye]] fluorescing agent which is a 5-carboxyfluorescein, 6-carboxyfluorescein, fluorexon, lissamine green, indocyanine green, rose bengal or mixture thereof.
5. (Original) The method of Claim 1 wherein said hydrophobic lubricant is a silicone based lubricant.
6. (Original) The method of Claim 1 wherein said hydrophobic lubricant is a polydimethylsiloxane.
7. (Original) The method of Claim 6 wherein said polydimethylsiloxane is utilized in combination with a crosslinkable silicone.
8. (Original) The method of Claim 1 wherein said mixture further comprises a surfactant.
9. (Original) The method of Claim 8 wherein said surfactant is biocompatible.
10. (Original) The method of Claim 8 wherein said surfactant is nonionic.
11. (Original) The method of Claim 10 wherein said surfactant is an ethylene oxide/propylene oxide block copolymer.

**BEST AVAILABLE COPY**

Application No. 09/908070  
Page 3

Amendment  
Attorney Docket No. S63.2B-9826-US01

12. (Previously Presented) A method for detecting the presence and uniformity of a lubricious coating on a medical device comprising the steps of:

- a) preparing a mixture of at least one fluorescing agent and mixtures thereof and at least one lubricant using a cosolvent blend;
- b) applying said mixture to the surface of a medical device to form a coating capable of exhibiting fluorescence; and
- c) subjecting the surface of the medical device to a source of energy capable of inducing a fluorescent emission; and
- d) observing the fluorescent emission to determine the location, uniformity or both of said lubricant.

13. (Original) The method of Claim 12 wherein said cosolvent blend comprises at least one alcohol and at least one straight chain hydrocarbon.

14. (Original) The method of Claim 13 wherein said at least one alcohol is isopropanol and said at least one hydrocarbon is heptane, hexane or a mixture thereof.

15- 38. (Canceled)

39. (Previously Presented) The method of claim 1 wherein said fluorescing agent is hydrophilic.

40. (Currently Amended) A method for detecting the presence and uniformity of a lubricious coating on a medical device comprising the steps of:

- a) preparing a mixture of at least one hydrophilic fluorescing agent and mixtures thereof and at least one hydrophobic lubricant;
- b) applying said mixture to the surface of a medical device to form a coating capable of exhibiting fluorescence; and
- c) subjecting the surface of the medical device to a source of energy capable of inducing a fluorescent emission; and
- d) observing the fluorescent emission to determine the location, uniformity or both of said lubricant.

41. (Withdrawn) A method for detecting the presence and uniformity of a lubricious coating on a medical device comprising the steps of:

- a) preparing a mixture of at least one fluorescing agent which is a member selected from the group consisting of fused aromatic compounds, phenyls, biphenyls,

Application No. 09/908070  
Page 4

Amendment  
Attorney Docket No. S63.2B-9826-US01

distyrylbenzenes, naphthalimides, carbozoles, pyrazolines, oxazoles, furans, benzo[*b*]furans, benzimidazoles, benzoxazoles, stilbenes, thiazoles, polymethines, quinolines, pyridines, pyridinium salts, flavones, acridones, xanthiones, dihydropyrimidines, acridines, cyanines, oxonols, resorofins, derivatives thereof and mixtures thereof and at least one lubricant;

- b) applying said mixture to the surface of a medical device to form a coating capable of exhibiting fluorescence; [[and]]
- c) subjecting the surface of the medical device to a source of energy capable of inducing a fluorescent emission; and
- d) observing the fluorescent emission to determine the location, uniformity or both of said lubricant.

42. (Withdrawn) The method of claim 41 wherein said fluorescing agent is a polymethine selected from the group consisting of cyanines, oxonols, styryls, derivatives thereof and mixtures thereof.

43. (New) A method for detecting the presence and uniformity of a lubricious coating on a medical device comprising the steps of:

- a) preparing a mixture of at least one fluorescing agent and at least one hydrophilic lubricant;
- b) applying said mixture to the surface of a medical device to form a coating capable of exhibiting fluorescence; and
- c) subjecting the surface of the medical device to a source of energy capable of inducing a fluorescent emission; and
- d) observing the fluorescent emission to determine the location, uniformity or both of said lubricant.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**